

HPCO₂ Component Description

75 and 100 lbm Capacity Carbon Dioxide Cylinder and Valve Assemblies

Effective: June 2020
K-81-1010 Rev AE

FEATURES

- US DOT 3AA-2300 Specification
- TC 3AM-176 Specification
- Type I Valve, 5/8"
- Straight Siphon Tube
- Underwriters' Laboratories Listed - File Number EX923
- United States Coast Guard Approved
- FM Approved, Standard 5420

DESCRIPTION

The Kidde Fire Systems High-Pressure Carbon Dioxide (CO₂) Fire Suppression System uses seamless steel cylinders to store carbon dioxide agent. The agent is stored under its own vapor pressure as a non-flammable compressed gas. Due to the physical properties of CO₂, both the vapor and liquid state are present within the cylinder. Each assembly is factory fitted with a discharge valve and siphon tube. A US DOT compliant safety relief device, protecting the cylinder from over pressurization, is provided as part of the discharge valve assembly. For shipment, a standard shipping cap is included, which mates to external threads on the cylinder neck to protect the discharge valve from inadvertent damage.

Prior to removing the shipping cap, each cylinder shall be properly secured using cylinder straps or Framing/Oak Rack Kits as required.

The discharge valve cannot dispense the cylinder contents without a properly attached discharge head. This feature provides an enhanced safeguard during transport. A discharge flex hose connects the discharge head to the system manifold. Alternatively, a swivel adapter may be used in place of a discharge flex hose to connect to the system manifold. One or more control heads will be required to actuate a manifold of cylinders.

After discharge, charging accessories are required to safely vent any residual pressure to service the discharge valve and then re-fill the cylinder.

SPECIFICATIONS

Service Pressure, Max: 2300-psi (158-bar)
Temperature, Min: 0°F (-17°C)
Temperature, Max: 130°F (55°C)

DIMENSIONS

Cylinder Capacity (lbm)	A Height (in.)	B Dia. (in.)
100	62.0"	10.50
75	60.0	9.25




Figure 1. Cylinder

ORDERING INFORMATION

Description	Application	Approvals	Part Number
Cylinder & Valve Assembly, 100-lbm	Industrial and Marine	UL/ULC FM Approvals USCG Various Class Societies	81-870269-000
Cylinder & Valve Assembly, 75-lbm			81-870287-000

REFERENCED COMPONENTS

Description	Reference Data Sheet
Discharge Head, Plain Nut	K-81-1060
Discharge Head, Grooved Nut	K-81-1070
Hose, 3/4" Outlet Discharge	K-81-1090
Adapter, Swivel	K-81-1105
Strap, Single Cylinder	K-81-1230
Strap, Dual Cylinder	K-81-1240
Framing Kit, Steel	See manual 81-CO2MAN-001
Rack Kit, Oak	See manual 220610
Control Head, Electric	K-81-8010*
Control Head, Cable Operated	K-81-6020*
Valve, 5/8" Type I (spare only)	K-81-1050
Fixture, Blow-Off	K-81-9110
Adapter, Charging	
* Typical listed, see referenced manuals for all applicable control heads.	

EXPORT INFORMATION (USA)

Jurisdiction: EAR
Classification: EAR99

This document contains technical data subject to the EAR.

All trademarks are the property of their respective owners.

This literature is provided for informational purposes only. KIDDE-FENWAL, INC. believes this data to be accurate, but it is published and presented without any guarantee or warranty whatsoever. KIDDE-FENWAL, INC. assumes no responsibility for the product's suitability for a particular application. The fire suppression system design, installation, maintenance, service and troubleshooting must be performed by trained, authorized Kidde Fire Systems distributors for the product to work correctly. If you need more information on this product, or if you have a particular problem or question, contact: KIDDE-FENWAL, INC., Ashland, MA 01721 USA, Telephone: (508) 881-2000.